


RACE
APPLICATION
ONLY

726

01-07 GM DURAMAX 6.6L 4" DUAL WITH HANGERS (DUALY TRUCKS)



- | | |
|---------------------------------------|---------------------------------------|
| <input type="checkbox"/> 1-10111(2-1) | <input type="checkbox"/> 8-LJ400 |
| <input type="checkbox"/> 1-10123(2-2) | <input type="checkbox"/> 2-H2 |
| <input type="checkbox"/> 1-2543 | <input type="checkbox"/> 1-9104(1-1) |
| <input type="checkbox"/> 1-10118(2-1) | <input type="checkbox"/> 1-40016(1-1) |
| <input type="checkbox"/> 1-10139(2-1) | |
| <input type="checkbox"/> 1-10120(2-1) | |
| <input type="checkbox"/> 1-10131(2-1) | |

FLO~PRO
PERFORMANCE EXHAUST

PICKED BY: _____



**WARNING: BEFORE YOUR BEGIN, VERIFY
THAT YOU RECEIVED THE RIGHT KIT &
EACH PART LISTED ON THE REVERSE PAGE**



**KIT #726
2001 -2007 GM 4" DUAL SYSTEM
(DUALY TRUCKS)**

REMOVAL OF ORIGINAL SYSTEM

1. Starting at the bottom of the turbo direct pipe, remove the band clamp from down pipe. Loosen the bolt enough to unlatch the clamp, then pry the clamp away from the flange at three spots with a flathead screwdriver. Remove clamp. **(Note: keep the stock band clamp, as it will be used with the new system).**
2. Cut the exhaust in two places, first the down pipe next to the transmission and second in front of the muffler. Spray the hangers with WD-40 or Loosen-All and then pry hangers from the rubber and remove the factory exhaust. **(Note: a sawzall or hacksaw is the preferred method of cutting exhaust).**

INSTALLATION INSTRUCTIONS

1. Install pipe #10111 using the factory turbo band clamp. Snug the clamp down so it will hold pipe but pipe can still be moved. Be sure to insert rod into hanger.
2. Temporarily hang muffler in factory rubber hanger. You will need to support the front of the muffler so that the muffler is level with the truck frame and hanging straight with rubber hanger.
3. Now that the muffler is supported and level with truck frame, install part #10123. **(Note: install hanger into factory rubber hanger).** Put on the clamp and snug it down so it will hold the pipe but the pipe can still be moved with some effort.
 - For Crew Cab Short Box wheelbase, pipe #40016 will be needed.
 - For Crew Cab Long Box wheel bases, pipe# 40016 and #9104 will be needed.
4. Install muffler on factory rubber hanger. Slip inlet over rear of pipe #10123, place clamp on inlet, snug the clamp down so it will hold muffler but the pipe can still be moved with some effort.
5. Install tail pipe #10120 into right side outlet of muffler and right side of truck.
6. Install tail pipe #10131 onto pipe #10120. **(Note: hanger is bolted from inside the frame using factory hole in the frame above the hanger on pipe #10131).**
7. Install pipe #10118 into left outlet of muffler.
8. Install tail pipe #10139 onto pipe #10118. **(Note: the hanger is bolted from inside the frame using the factory hole in frame above the hanger on pipe #10139).**
9. Install all clamps on both tail pipes. Snug the clamps down so they will hold the pipe but the pipe can still be moved with some effort.
10. **Check for clearances, i.e. brake lines may have to be moved, or e-brake cables as well as axle vent tube.** Also check to make sure that the exit of tail pipes is level with truck.
11. Starting with pipe #10111, tighten turbo band clamp then starting at front clamp, work your way to the back connection, tightening as you go. **(Note: A mig weld should be applied to the clamped connections of pipe for added security). DO NOT WELD CLAMPS.**

Note: Universal converter adapter kit #4000 is required on all converter-equipped models.

www.flopro.com

Technical Support: 1 800 762 4286 or email, techsupport@flopro.com